




LOW PRICE

CALL

781-858-1155

DRYTECH 300 – 360 – 500 – 900 / SOFT MOUNTED / STILL

At  we strongly believe that the fastest way to achieve a complete cycle is to extract the maximum amount of solvent before the drying cycle. Our state of the art electronic balancing system will achieve extraction speeds up to 850 rpm (at 344 G factor) balancing full loads as well as partial loads.

The variable speed drive gives you the flexibility to program different wash speeds and customize programs for washing every kind of fabric.

MODEL	DRYTECH	300	360	500	900
Load capacity	kg	15	18	25	40
	lb	33	40	55	88
DRUM					
Volume	dm ³	300	362	503	800
Extract speed	g/l'	850	850	800	750
Still	lt	100	190	290	420
TANKS					
1st Tank	lt	120	140	180	320
2nd Tank	lt	120	140	180	320
3rd Tank	lt	150	180	245	350
DIMENSIONS					
Width	mm	1750	2110	2260	2900
Depth	mm	1500	1500	1800	2000
Height	mm	2037	2115	2320	2500
INSTALLED POWER					
Steam model	kw	5.5	8	10	11
Electric model	kw	15	25	30	-
Weight	kg	1750	2000	2700	4800
	lb	3850	4400	5940	10560

